

Z300 ABS



Please note the image shown above is for illustration purposes only.

Specifications

ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke Parallel Twin	Type	Tube diamond, steel
Displacement	296 cm ³	Caster (rake)	26.0°
Bore and Stroke	62.0 x 49.0 mm	Tyre:	
Compression Ratio	10.6:1	a) Front	110/70-17M/C 54S
Valve System	DOHC, 8 valves	b) Rear	140/70-17M/C 66S
a) Maximum power	29.0 kW {39 PS} / 11,000 min ⁻¹	Wheel travel: front	120 mm
b) Maximum torque	27.0 N.m {2.8 kgf.m} / 10,000 min ⁻¹	rear	132 mm
Fuel System	Fuel injection: ø32 mm x 2, with dual throttle valves	Steering angle (left/right)	35° / 35°
Ignition	Digital	SUSPENSION	
Starting	Electric	Front: Type	ø37 mm telescopic fork
Lubrication	Forced lubrication, wet sump	Rear: Type	Bottom-Link Uni-Trak with gas-charged shock and adjustable preload
DRIVE TRAIN		BRAKES	
Transmission	6-speed, return	Front: Type	Single ø290 mm petal disc
Final Drive:	Chain	Caliper	Single balanced actuation dual-piston
Primary Reduction Ratio	3.087 (71/23)	Rear: Type	Single ø220 mm petal disc
Gear ratios:		Caliper	Dual-piston
1st	2.714 (38/14)	DIMENSIONS	
2nd	1.789 (34/19)	Overall length	2,015 mm
3rd	1.409 (31/22)	Overall width	750 mm
4th	1.160 (29/25)	Overall height	1,025 mm
5th	1.000 (27/27)	Wheelbase	1,405 mm
6th	0.857 (24/28)	Ground clearance	145 mm
Final reduction ratio	3.000 (42/14)	Seat height	785 mm
Clutch	Wet multi-disc, manual	Curb mass	170 kg
		Fuel capacity	17 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.